

# SAFETY DATA SHEET

# PETTIT



Revision Date 01-Jan-2019  
Version 1

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** Pettit Protect Epoxy Primer White 4100 - Part A  
**Product code** 1410000

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use** Primers  
**Restrictions on use** No information available

### 1.3 Details of the supplier of the safety data sheet

**Supplier** Kop-Coat, Inc./ Pettit Marine Paint  
Marine Group  
36 Pine Street  
Rockaway, NJ 07866  
1-800-221-4466

### 1.4 Emergency telephone number

**Emergency telephone number** Chemtrec: +1 703-527-3887 ex-USA  
Chemtrec: 1-800-424-9300 USA

## 2. Hazards identification

### 2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 3

### 2.2 Label elements

**Signal Word**

Danger

**Hazard Statements**

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause cancer

Suspected of damaging fertility or the unborn child

May cause damage to organs through prolonged or repeated exposure

Flammable liquid and vapor

**Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

**Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Wash contaminated clothing before reuse

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish**Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**2.3. Other Hazards Hazards not otherwise classified (HNOC)**

Not Applicable

**2.4 Other information**

Not Applicable

**Unknown Acute Toxicity**

&lt; 1% of the mixture consists of ingredient(s) of unknown toxicity

### 3. Composition/Information on Ingredients

**Substance**

Not applicable

**Mixture**

Chemical Name	CAS-No	Weight %
REACTION PRODUCT: BISPHENOL F-(EPICHLORHYDRIN) MW <= 700	28064-14-4	20 - 30
Barium Sulfate	7727-43-7	10 - 20
Titanium dioxide	13463-67-7	10 - 20
Xylene	1330-20-7	10 - 20
Mica	12001-26-2	10 - 20
Talc	14807-96-6	5 - 10
MAGNESITE	546-93-0	1 - 5
Ethylbenzene	100-41-4	1 - 5
Ethylene glycol monobutyl ether	111-76-2	1 - 5
Crystalline silica (quartz)	14808-60-7	< 1
Toluene	108-88-3	< 1

The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

### 4.1 Description of first-aid measures

<b>General advice</b>	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a physician or poison control center immediately.
<b>Skin contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician or poison control center immediately. Wash contaminated clothing before reuse.
<b>Inhalation</b>	Move victim to fresh air. If not breathing, give artificial respiration. Keep victim warm and quiet. Call a physician or poison control center immediately.
<b>Ingestion</b>	Gently wipe or rinse the inside of the mouth with water. Never give fluids if the victim is unconscious or having convulsions. Do NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position. Call a physician or poison control center immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

**Symptoms** See Section 2.2, Label Elements and/or Section 11, Toxicological effects.

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** There is no specific antidote for effects from overexposure to this material. Treat symptomatically.

## 5. Fire-Fighting Measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

**Unsuitable Extinguishing Media** Water may be unsuitable for extinguishing fires.

### 5.2 Special hazards arising from the substance or mixture

**Special Hazard**

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to areas away from work site before igniting/flashing back to vapor source Thermal decomposition can lead to release of irritating gases and vapors

**Hazardous Combustion Products** Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

**Explosion Data**

**Sensitivity to Mechanical Impact** Not sensitive.

**Sensitivity to Static Discharge** Yes.

**5.3 Advice for firefighters**

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished. Corrosive hazard. Wear protective gloves/clothing and eye/face protection.

## 6. Accidental Release Measures

**6.1 Personal precautions, protective equipment and emergency procedures**

Do not get in eyes, on skin, or on clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ensure adequate ventilation, especially in confined areas. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Keep people away from and upwind of spill/leak. Stop leak if you can do it without risk. Wear protective gloves/clothing and eye/face protection. Thoroughly decontaminate all protective equipment after use. Ensure adequate ventilation, especially in confined areas.

**6.2 Environmental precautions**

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

**6.3 Methods and materials for containment and cleaning up****Methods for Containment**

Dike to collect large liquid spills. Prevent further leakage or spillage if safe to do so. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

**Methods for cleaning up**

Take up with sand, earth or other noncombustible absorbent material. Clean contaminated surface thoroughly.

## 7. Handling and storage

**7.1 Precautions for safe handling****Advice on safe handling**

Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Ground and bond containers when transferring material. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking.

**Hygiene measures**

Do not get in eyes, on skin, or on clothing.

**7.2 Conditions for safe storage, including any incompatibilities****Storage Conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations.

**Materials to Avoid**

No materials to be especially mentioned.

**8. Exposure controls/personal protection****8.1 Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Barium Sulfate 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm
Mica 12001-26-2	TWA: 3 mg/m <sup>3</sup> respirable fraction	TWA: 20 mppcf <1% Crystalline silica	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>
Talc 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
MAGNESITE 546-93-0	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>		TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 20 ppm
Ethylene glycol monobutyl ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> S*	TWA: 20 ppm	TWA: 20 ppm TWA: 97 mg/m <sup>3</sup>	TWA: 20 ppm TWA: 97 mg/m <sup>3</sup>	TWA: 20 ppm
Crystalline silica (quartz) 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	: (30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA total dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.10 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	TWA: 20 ppm Adverse reproductive effect	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> Skin	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> Skin	TWA: 20 ppm

**8.2 Appropriate engineering controls****Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Apply technical measures to comply with the occupational exposure limits.

**8.3 Individual protection measures, such as personal protective equipment**

<b>Eye/Face Protection</b>	Tightly fitting safety goggles.
<b>Skin and body protection</b>	Wear impervious gloves and/or clothing if needed to prevent contact with the material. Neoprene gloves. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Long sleeved clothing. Chemical resistant apron. Protective shoes or boots. Remove and wash contaminated clothing before re-use.
<b>Respiratory protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.
<b>Hygiene measures</b>	See section 7 for more information

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	viscous
<b>Color</b>	White
<b>Odor</b>	Hydrocarbon-like
<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
<b>pH</b>	Not applicable	
<b>Melting/freezing point</b>		No information available
<b>Boiling point/boiling range</b>	> 100 °C / 212 °F	
<b>Flash Point</b>	35 °C / 95 °F	
<b>Evaporation rate</b>		No information available
<b>Flammability (solid, gas)</b>		No information available
<b>Flammability Limits in Air</b>		
upper flammability limit		No information available
lower flammability limit		No information available
<b>Vapor pressure</b>		No information available
<b>Vapor density</b>		No information available
<b>Specific Gravity</b>		No information available
<b>Water solubility</b>		No information available
<b>Solubility in other solvents</b>		No information available
<b>Partition coefficient</b>		No information available
<b>Autoignition temperature</b>		No information available
<b>Decomposition temperature</b>		No information available
<b>Viscosity, kinematic</b>	> 22 mm <sup>2</sup> /s	
<b>Viscosity, dynamic</b>		No information available
<b>Explosive properties</b>		No information available
<b>Oxidizing Properties</b>		No information available

### 9.2 Other information

<b>Volatile organic compounds (VOC) content</b>	338 g/L
<b>Density</b>	14.65 lb/gal

## 10. Stability and Reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use

### 10.2 Chemical stability

Stable under recommended storage conditions

**10.3 Possibility of hazardous reactions**

None under normal processing.

**10.4 Conditions to Avoid**

None known based on information supplied.

**10.5 Incompatible Materials**

No materials to be especially mentioned.

**10.6 Hazardous Decomposition Products**

Thermal decomposition can lead to release of toxic/corrosive gases and vapors.

## 11. Toxicological information

**11.1 Acute toxicity****Numerical measures of toxicity: Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

**Unknown Acute Toxicity** < 1% of the mixture consists of ingredient(s) of unknown toxicity

<b>Oral LD50</b>	13,415.00 mg/kg
<b>Dermal LD50</b>	26,078.00 mg/kg
<b>LC50 (Vapor)</b>	68.00 mg/l

**Numerical measures of toxicity: Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Barium Sulfate 7727-43-7	> 5005 mg/kg (rat)	-	-
Titanium dioxide 13463-67-7	10000 mg/kg ( Rat )	-	-
Xylene 1330-20-7	3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
Ethylbenzene 100-41-4	3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
Ethylene glycol monobutyl ether 111-76-2	470 mg/kg ( Rat )	= 2000 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h
Toluene 108-88-3	2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 28.1 mg/L ( Rat ) 4 h

**11.2 Information on toxicological effects****Skin corrosion/irritation**

Product Information

Not formulated or available

Component Information

Not formulated or available

**Eye damage/irritation**

Product Information

Not formulated or available

Component Information

Not formulated or available

**Respiratory or skin sensitization**

Product Information

- No information available

Component Information

- No information available

**Germ cell mutagenicity**Product Information

- No information available

Component Information

- No information available

**Carcinogenicity**Product Information

- The table below indicates whether each agency has listed any ingredient as a carcinogen

Component Information

- Contains a known or suspected carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	
Ethylbenzene 100-41-4	-	Group 2B	-	
Crystalline silica (quartz) 14808-60-7	A2	Group 1	Known	

**Reproductive toxicity**Product Information

- No information available

Component Information

- No information available

**STOT - single exposure**

No information available

**STOT - repeated exposure**

- No information available

**Other adverse effects**Product Information

- No information available

Component Information

- No information available

**Aspiration hazard**Product Information

- No information available

Component Information

- No information available

## 12. Ecological information

**12.1 Toxicity****Ecotoxicity**

No information available

20.3688398 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

**Ecotoxicity effects**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Xylene	-	LC50: 96 h Pimephales promelas	EC50: 48 h water flea 3.82 mg/L



1330-20-7		23.53 - 29.97 mg/L static LC50: 96 h Cyprinus carpio 780 mg/L semi-static LC50: 96 h Cyprinus carpio 780 mg/L LC50: 96 h Poecilia reticulata 30.26 - 40.75 mg/L static LC50: 96 h Pimephales promelas 13.4 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L static LC50: 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L LC50: 96 h Lepomis macrochirus 13.1 - 16.5 mg/L flow-through LC50: 96 h Lepomis macrochirus 19 mg/L LC50: 96 h Lepomis macrochirus 7.711 - 9.591 mg/L static	LC50: 48 h Gammarus lacustris 0.6 mg/L
Talc 14807-96-6	-	LC50: 96 h Brachydanio rerio 100 g/L semi-static	-
Ethylbenzene 100-41-4	EC50: 72 h Pseudokirchneriella subcapitata 4.6 mg/L EC50: 96 h Pseudokirchneriella subcapitata 438 mg/L EC50: 72 h Pseudokirchneriella subcapitata 2.6 - 11.3 mg/L static EC50: 96 h Pseudokirchneriella subcapitata 1.7 - 7.6 mg/L static	LC50: 96 h Oncorhynchus mykiss 11.0 - 18.0 mg/L static LC50: 96 h Oncorhynchus mykiss 4.2 mg/L semi-static LC50: 96 h Pimephales promelas 7.55 - 11 mg/L flow-through LC50: 96 h Lepomis macrochirus 32 mg/L static LC50: 96 h Pimephales promelas 9.1 - 15.6 mg/L static LC50: 96 h Poecilia reticulata 9.6 mg/L static	EC50: 48 h Daphnia magna 1.8 - 2.4 mg/L
Ethylene glycol monobutyl ether 111-76-2	-	LC50: 96 h Lepomis macrochirus 1490 mg/L static LC50: 96 h Lepomis macrochirus 2950 mg/L	EC50: 48 h Daphnia magna 1000 mg/L
Toluene 108-88-3	EC50: 96 h Pseudokirchneriella subcapitata 433 mg/L EC50: 72 h Pseudokirchneriella subcapitata 12.5 mg/L static	LC50: 96 h Pimephales promelas 15.22 - 19.05 mg/L flow-through LC50: 96 h Pimephales promelas 12.6 mg/L static LC50: 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L static LC50: 96 h Oncorhynchus mykiss 5.8 mg/L semi-static LC50: 96 h Lepomis macrochirus 11.0 - 15.0 mg/L static LC50: 96 h Oryzias latipes 54 mg/L static LC50: 96 h Poecilia reticulata 28.2 mg/L semi-static LC50: 96 h Poecilia reticulata 50.87 - 70.34 mg/L static	EC50: 48 h Daphnia magna 5.46 - 9.83 mg/L Static EC50: 48 h Daphnia magna 11.5 mg/L

## 12.2 Persistence and degradability

No information available.

## 12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
Xylene 1330-20-7	3.15
Ethylbenzene 100-41-4	3.118
Ethylene glycol monobutyl ether 111-76-2	0.81
Toluene 108-88-3	2.65

## 12.4 Mobility in soil

No information available.

**12.5 Other adverse effects**

No information available

**13. Disposal Considerations****13.1 Waste treatment methods**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**14. Transport Information**

<b>Note</b>	Limited quantity This product may be reclassified as Consumer Commodity, ORM-D, when shipped by ground; packaging quantity limitations apply.
<b>DOT</b> Proper shipping name	Quarts and gallons ship as limited quantity. UN1263, Paint, 3, III
<b>MEX</b>	no data available
<b>IMDG</b> Proper shipping name	UN1263, Paint, 3, III
<b>IATA</b> Proper shipping name	UN1263, Paint, 3, III

**15. Regulatory information****15.1 International Inventories**

<b>TSCA</b>	Complies
<b>DSL</b>	-
<b>EINECS/ELINCS</b>	-
<b>ENCS</b>	-
<b>IECSC</b>	-
<b>KECL</b>	-
<b>PICCS</b>	-
<b>AICS</b>	-
<b>NZIoC</b>	-

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

**15.2 U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Barium Sulfate 7727-43-7	1.0
Xylene 1330-20-7	1.0

Ethylbenzene 100-41-4	0.1
Ethylene glycol monobutyl ether 111-76-2	1.0

**15.3 Pesticide Information**

Not applicable

**15.4 U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
Crystalline silica (quartz) - 14808-60-7	Carcinogen
Toluene - 108-88-3	Developmental Female Reproductive
Crystalline silica (Quartz) (Respirable) - 14808-60-7	Carcinogen
CUMENE - 98-82-8	Carcinogen
Benzene - 71-43-2	Carcinogen Developmental Male Reproductive

**16. Other information**

<b>NFPA</b>	<b>Health Hazard</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	<b>Physical and chemical hazards -</b> <b>Personal protection</b> X
<b>HMIS</b>	<b>Health Hazard</b> 2*	<b>Flammability</b> 3	<b>Physical Hazard</b> 0	

**Legend:**

ACGIH (American Conference of Governmental Industrial Hygienists)

Ceiling (C)

DOT (Department of Transportation)

EPA (Environmental Protection Agency)

IARC (International Agency for Research on Cancer)

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG)

NIOSH (National Institute for Occupational Safety and Health)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEL (Permissible Exposure Limit)

Reportable Quantity (RQ)

Skin designation (S\*)

STEL (Short Term Exposure Limit)

TLV® (Threshold Limit Value)

TWA (time-weighted average)

**Revision Date** 01-Jan-2019**Revision Note**

No information available

**Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**

# SAFETY DATA SHEET

# PETTIT



Revision Date 01-Jan-2019  
Version 1

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** Pettit Protect Epoxy Primer 4101 White - Part B  
**Product code** 1410108

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use** Primers  
**Restrictions on use** No information available

### 1.3 Details of the supplier of the safety data sheet

**Supplier** Kop-Coat, Inc./ Pettit Paint  
Marine Group  
36 Pine Street  
Rockaway, NJ 07866  
1-800-221-4466

### 1.4 Emergency telephone number

**Emergency telephone number** Chemtrec: +1 703-527-3887 ex-USA  
Chemtrec: 1-800-424-9300 USA

## 2. Hazards identification

### 2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1A
Flammable liquids	Category 2

### 2.2 Label elements

**Signal Word**  
Danger

**Hazard Statements**

Causes skin irritation  
 Causes serious eye damage  
 May cause an allergic skin reaction  
 Highly flammable liquid and vapor

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Contaminated work clothing must not be allowed out of the workplace  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/Bond container and receiving equipment  
 Use explosion-proof electrical/ventilating/lighting/equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Wear protective gloves/eye protection/face protection

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 Immediately call a POISON CENTER or doctor

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Wash contaminated clothing before reuse

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam to extinguish

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**2.3. Other Hazards Hazards not otherwise classified (HNOC)**

Not Applicable

**2.4 Other information**

Not Applicable

**Unknown Acute Toxicity**

< 1% of the mixture consists of ingredient(s) of unknown toxicity

### 3. Composition/Information on Ingredients

**Substance**

Not applicable

**Mixture**

Chemical Name	CAS-No	Weight %
Polyamide epoxy adduct	Proprietary	50 - 60
Xylene	1330-20-7	10 - 20
n-Propanol	71-23-8	10 - 20
Amidoamine resin	Proprietary	1 - 5
2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL	90-72-2	1 - 5

3,6,9-TRIAZAUNDECAMETHYLENEDIAMINE	112-57-2	< 1
------------------------------------	----------	-----

The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

### 4.1 Description of first-aid measures

<b>General advice</b>	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a physician or poison control center immediately.
<b>Skin contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician or poison control center immediately. Wash contaminated clothing before reuse.
<b>Inhalation</b>	Move victim to fresh air. If not breathing, give artificial respiration. Keep victim warm and quiet. Call a physician or poison control center immediately.
<b>Ingestion</b>	Gently wipe or rinse the inside of the mouth with water. Never give fluids if the victim is unconscious or having convulsions. Do NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position. Call a physician or poison control center immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	See Section 2.2, Label Elements and/or Section 11, Toxicological effects.
-----------------	---

### 4.3 Indication of any immediate medical attention and special treatment needed

<b>Notes to physician</b>	There is no specific antidote for effects from overexposure to this material. Treat symptomatically.
---------------------------	--

## 5. Fire-Fighting Measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam. Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water spray or fog. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

**Unsuitable Extinguishing Media** Water may be unsuitable for extinguishing fires.

### 5.2 Special hazards arising from the substance or mixture

#### Special Hazard

Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to areas away from work site before igniting/flashing back to vapor source Thermal decomposition can lead to release of irritating gases and vapors

**Hazardous Combustion Products** Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

#### Explosion Data

**Sensitivity to Mechanical Impact** Not sensitive.

**Sensitivity to Static Discharge** Yes.

### 5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use.

DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished. Corrosive hazard. Wear protective gloves/clothing and eye/face protection.

## 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Do not get in eyes, on skin, or on clothing. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ensure adequate ventilation, especially in confined areas. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Keep people away from and upwind of spill/leak. Stop leak if you can do it without risk. Wear protective gloves/clothing and eye/face protection. Thoroughly decontaminate all protective equipment after use. Ensure adequate ventilation, especially in confined areas.

### 6.2 Environmental precautions

Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

### 6.3 Methods and materials for containment and cleaning up

<b>Methods for Containment</b>	Dike to collect large liquid spills. Prevent further leakage or spillage if safe to do so. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).
<b>Methods for cleaning up</b>	Take up with sand, earth or other noncombustible absorbent material. Clean contaminated surface thoroughly.

## 7. Handling and storage

### 7.1 Precautions for safe handling

<b>Advice on safe handling</b>	Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Ground and bond containers when transferring material. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. No smoking.
--------------------------------	--

<b>Hygiene measures</b>	Do not get in eyes, on skin, or on clothing.
-------------------------	--

### 7.2 Conditions for safe storage, including any incompatibilities

<b>Storage Conditions</b>	Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in properly labeled containers. Keep away from food, drink and animal feedingstuffs. Store in accordance with local regulations.
---------------------------	--

<b>Materials to Avoid</b>	No materials to be especially mentioned.
---------------------------	--

## 8. Exposure controls/personal protection

### 8.1 Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm

				STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	
n-Propanol 71-23-8	TWA: 100 ppm	TWA: 200 ppm TWA: 500 mg/m <sup>3</sup>	TWA: 100 ppm	TWA: 200 ppm TWA: 492 mg/m <sup>3</sup> STEL: 400 ppm STEL: 984 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 492 mg/m <sup>3</sup> STEL: 250 ppm STEL: 614 mg/m <sup>3</sup> Skin	TWA: 100 ppm

**8.2 Appropriate engineering controls**

**Engineering Measures**                      Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Apply technical measures to comply with the occupational exposure limits.

**8.3 Individual protection measures, such as personal protective equipment**

- Eye/Face Protection**                      Tightly fitting safety goggles.
- Skin and body protection**                      Wear impervious gloves and/or clothing if needed to prevent contact with the material. Neoprene gloves. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Long sleeved clothing. Chemical resistant apron. Protective shoes or boots. Remove and wash contaminated clothing before re-use.
- Respiratory protection**                      If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.
- Hygiene measures**                              See section 7 for more information



## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	No information available
<b>Color</b>	Amber
<b>Odor</b>	Hydrocarbon-like
<b>Odor Threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
<b>pH</b>	Not applicable	
<b>Melting/freezing point</b>		No information available
<b>Boiling point/boiling range</b>	> 100 °C / 212 °F	
<b>Flash Point</b>	18 °C / 64 °F	
<b>Evaporation rate</b>		No information available
<b>Flammability (solid, gas)</b>		No information available
<b>Flammability Limits in Air</b>		
upper flammability limit		No information available
lower flammability limit		No information available
<b>Vapor pressure</b>		No information available
<b>Vapor density</b>		No information available
<b>Specific Gravity</b>		No information available
<b>Water solubility</b>		No information available
<b>Solubility in other solvents</b>		No information available
<b>Partition coefficient</b>		No information available
<b>Autoignition temperature</b>		No information available
<b>Decomposition temperature</b>		No information available
<b>Viscosity, kinematic</b>	> 22 mm <sup>2</sup> /s	
<b>Viscosity, dynamic</b>		No information available
<b>Explosive properties</b>		No information available
<b>Oxidizing Properties</b>		No information available

### 9.2 Other information

<b>Volatile organic compounds (VOC) content</b>	340 g/L
<b>Density</b>	7.72 lb/gal

## 10. Stability and Reactivity

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use

### 10.2 Chemical stability

Stable under recommended storage conditions

### 10.3 Possibility of hazardous reactions

None under normal processing.

### 10.4 Conditions to Avoid

None known based on information supplied.

### 10.5 Incompatible Materials

No materials to be especially mentioned.

### 10.6 Hazardous Decomposition Products

Thermal decomposition can lead to release of toxic/corrosive gases and vapors.

## 11. Toxicological information

### 11.1 Acute toxicity

#### Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

**Unknown Acute Toxicity** < 1% of the mixture consists of ingredient(s) of unknown toxicity

<b>Oral LD50</b>	15,197.00 mg/kg
<b>Dermal LD50</b>	19,002.00 mg/kg
<b>LC50 (Vapor)</b>	58.00 mg/l

#### Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Xylene 1330-20-7	3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
n-Propanol 71-23-8	3830 mg/kg ( Rat )	> 10000 mg/kg ( Rabbit )	> 13548 ppm ( Rat ) 4 h
2,4,6-TRIS(DIMETHYLAMINOMET HYL)PHENOL 90-72-2	1000 mg/kg ( Rat )	= 1280 mg/kg ( Rat )	-
3,6,9-TRIAZAUNDECAMETHYLEN EDIAMINE 112-57-2	2100 mg/kg ( Rat )	= 660 µL/kg ( Rabbit )	-

### 11.2 Information on toxicological effects

#### Skin corrosion/irritation

Product Information

N o format raøai bl ae

Component Information

N o format raøai bl ae

#### Eye damage/irritation

Product Information

N o format raøai bl ae

Component Information

N o format raøai bl ae

#### Respiratory or skin sensitization

Product Information

N o format raøai bl ae

Component Information

N o format raøai bl ae

#### Germ cell mutagenicity

Product Information

N o format raøai bl ae

Component Information

N o format raøai bl ae

#### Carcinogenicity

Product Information

N o format raøai bl ae

Component Information

N o format raøai bl ae

**Reproductive toxicity**Product Information

- No information available

Component Information

- No information available

**STOT - single exposure**

No information available

**STOT - repeated exposure**

No information available

**Other adverse effects**Product Information

- No information available

Component Information

- No information available

**Aspiration hazard**Product Information

- No information available

Component Information

- No information available

**12. Ecological information****12.1 Toxicity****Ecotoxicity**

No information available

61.6645 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

**Ecotoxicity effects**

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Xylene 1330-20-7	-	LC50: 96 h Pimephales promelas 23.53 - 29.97 mg/L static LC50: 96 h Cyprinus carpio 780 mg/L semi-static LC50: 96 h Cyprinus carpio 780 mg/L LC50: 96 h Poecilia reticulata 30.26 - 40.75 mg/L static LC50: 96 h Pimephales promelas 13.4 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 2.661 - 4.093 mg/L static LC50: 96 h Oncorhynchus mykiss 13.5 - 17.3 mg/L LC50: 96 h Lepomis macrochirus 13.1 - 16.5 mg/L flow-through LC50: 96 h Lepomis macrochirus 19 mg/L LC50: 96 h Lepomis macrochirus 7.711 - 9.591 mg/L static	EC50: 48 h water flea 3.82 mg/L LC50: 48 h Gammarus lacustris 0.6 mg/L
n-Propanol 71-23-8	-	LC50: 96 h Pimephales promelas 4480 mg/L flow-through	EC50: 48 h Daphnia magna 3642 mg/L EC50: 48 h Daphnia magna 3339 - 3977 mg/L Static
3,6,9-TRIAZAUNDECAMETHYLENEDIAMINE 112-57-2	EC50: 72 h Pseudokirchneriella subcapitata 2.1 mg/L	LC50: 96 h Poecilia reticulata 420 mg/L static	EC50: 48 h Daphnia magna 24.1 mg/L

**12.2 Persistence and degradability**

No information available.

**12.3 Bioaccumulative potential**

Discharge into the environment must be avoided

Chemical Name	log Pow
Xylene 1330-20-7	3.15
n-Propanol 71-23-8	0.34
3,6,9-TRIAZAUNDECAMETHYLENEDIAMINE 112-57-2	1

**12.4 Mobility in soil**

No information available.

**12.5 Other adverse effects**

No information available

**13. Disposal Considerations****13.1 Waste treatment methods**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

**14. Transport Information**

**Note** Limited quantity This product may be reclassified as Consumer Commodity, ORM-D, when shipped by ground; packaging quantity limitations apply.

**DOT**  
**Proper shipping name** Quarts ship as limited quantity  
UN1263, Paint, 3, II

**MEX**  
no data available

**IMDG**  
**Proper shipping name** UN1263, Paint, 3, II

**IATA**  
**Proper shipping name** UN1263, Paint, 3, II

**15. Regulatory information****15.1 International Inventories**

<b>TSCA</b>	Complies
<b>DSL</b>	Complies
<b>EINECS/ELINCS</b>	-
<b>ENCS</b>	-
<b>IECSC</b>	-
<b>KECL</b>	-
<b>PICCS</b>	-
<b>AICS</b>	-
<b>NZIoC</b>	-

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

## 15.2 U.S. Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
Xylene 1330-20-7	1.0

## 15.3 Pesticide Information

Not applicable

## 15.4 U.S. State Regulations

### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

## 16. Other information

<b>NFPA</b>	<b>Health Hazard</b> 3	<b>Flammability</b> 3	<b>Instability</b> 0	<b>Physical and chemical hazards - Personal protection</b> X
<b>HMIS</b>	<b>Health Hazard</b> 3	<b>Flammability</b> 3	<b>Physical Hazard</b> 0	

### **Legend:**

*ACGIH (American Conference of Governmental Industrial Hygienists)*

*Ceiling (C)*

*DOT (Department of Transportation)*

*EPA (Environmental Protection Agency)*

*IARC (International Agency for Research on Cancer)*

*International Air Transport Association (IATA)*

*International Maritime Dangerous Goods (IMDG)*

*NIOSH (National Institute for Occupational Safety and Health)*

*NTP (National Toxicology Program)*

*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*

*PEL (Permissible Exposure Limit)*

*Reportable Quantity (RQ)*

*Skin designation (S\*)*

*STEL (Short Term Exposure Limit)*

*TLV® (Threshold Limit Value)*

*TWA (time-weighted average)*

**Revision Date** 01-Jan-2019

### **Revision Note**

No information available

### **Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**